State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-6-1054
Relating to Certification of New Motor Vehicles

GENERAL MOTORS CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below:

Model Year: 2002

Vehicle Type: 5751-8500 Pound Test Weight Medium-Duty Vehicle

Exhaust Emission Standard Category: Low-Emission Vehicle (LEV)

Fuel Type: Gasoline

Test Group: 2GMXA06.0194

Engine Displacement: 5.7 and 6.0 Liters

Evaporative Family (Evap): 1: 2GMXE0111908
2: 2GMXE0111911
3: 2GMXE0111920

Special Features and Exhaust Emission Control Systems (ECS):

ECS I	ECS II
Sequential Multiport Fuel Injection	Sequential Multiport Fuel Injection
Dual Three Way Catalytic Converters	Dual Three Way Catalytic Converters
Dual Heated Oxygen Sensors (two)	Dual Heated Oxygen Sensors (two)
Exhaust Gas Recirculation	Exhaust Gas Recirculation
Secondary Air Injection	

Models Covered:
5.7 Liters/Evap 1/ECS I: Chevrolet G1500/2500 Express Passenger 2WD, G1500/2500 Van Cargo 2WD; GMC G1500/2500 Savana Cargo 2WD, G1500/2500 Savana Passenger 2WD
6.0 Liters/Evap 2/ECS II: GMC K1500 Yukon Denali AWD, K1500 Centennial AWD; Cadillac Escalade AWD
6.0 Liters/Evap 3/ECS II: GMC K1500 Yukon XL AWD; Cadillac Escalade XLT EXT

The exhaust certification emission levels and standards, in grams per mile, of non-methane organic gases (NMOG), carbon monoxide (CO), oxides of nitrogen (NOx), and formaldehyde (HCHO) for the listed vehicle models are as follows. The NMOG exhaust certification emission levels include application of the reactivity adjustment factor (RAF) as specified.

The evaporative hydrocarbon (HC) certification emission levels and standards for three-day diurnal plus hot soak (3D) and two-day diurnal plus hot soak (2D) in grams per test, running loss (RL) in grams per mile, and onboard refueling vapor recovery (ORVR) in grams per gallon of fuel dispensed, for the listed vehicle models are as follows.

Type of Emissions	Miles	Certification Level	Certification Standards
EXHAUST @ NMOG RAF = 0.94			
NMOG	50,000	0.089	0.195
NMOG	120,000	0.113	0.280
CO	50,000	1.9	5.0
CO	120,000	2.6	7.3
NOx	50,000	0.3	0.6
NOx.	120,000	0.5	0.9
NOx (highway)	50,000	0.1	1.2
NOx (highway)	120,000	0.3	1.8
HCHO	50,000	0.002	0.022
..... HCHO	120,000	0.003	0.032
..... CO (20°F)	50,000	3.4	12.5
NMOG (50°F)	4,000	n/a	0.390
CO (50°F)	4,000	n/a	5.0
NOx (50°F)	4,000	n/a	0.6
HCHO (50°F)	4,000	n/a	0.044

EVAPORATIVE		Evap 1	Evap 2	Evap 3	Evap 1	Evap 2 & 3
HC-2D	120,000	1.2	1.4	2.2	3.0	2.5
HC-3D	120,000	1.3	1.3	1.6	2.5	2.0
HC-RL	120,000	0.00	0.00	0.00	0.05	0.05
HC-ORVR	120,000	n/a	n/a	n/a	n/a	n/a

BE IT FURTHER RESOLVED: That any "Vehicle Equivalent Debit" in the manufacturer's medium-duty vehicle phase-in compliance plan shall be equalized as required by the "California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the 50° Fahrenheit testing requirement for the listed vehicle models has been met based on the compliance plan submitted by the manufacturer in lieu of actual testing.

BE IT FURTHER RESOLVED: That the listed vehicle models are conditionally certified to the "Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines" (Title 13, California Code of Regulations, Section 1968.1). This certification is contingent upon the manufacturer providing the on-board diagnostic demonstration data required by Title 13, California Code of Regulations, Section 1968.1(g) by February 15, 2001. Failure to submit the required demonstration data by the specified date, or failure of the submitted demonstration data to show compliance with the test procedures, shall be cause for the Air Resources Board to revoke this Executive Order and vehicles sold under the revoked conditional certification shall be deemed uncertified.

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with the following California emission regulations and requirements. Vehicles certified under this Executive Order shall conform to all applicable California emission regulations and requirements.

- Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks (Title 13, California Code of Regulations, Section 2235)

- Motor Vehicle Emission Control and Smog Index Label Specifications (Title 13, California Code of Regulations, Section 1965)

- Emission Control System Warranty (Title 13, California Code of Regulations, Sections 2035 et seq.)

- High-Altitude Requirements and California Inspection and Maintenance Emission Standards (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles)

The Bureau of Automotive Repair will be notified by copy of this order.

Executed at El Monte, California this 18th day of December 2000.

R. B. Summerfield, Chief
Mobile Source Operations Division